## NSN 5970-01-597-5011

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-597-5011

**Reliability Indicator:** 

Not established

**Main Body Inside Diameter:** 

1.520 inches as supplied

First Branch Inside Diameter:

0.760 inches as supplied

**Second Branch Inside Diameter:** 

0.760 inches as supplied

**Third Branch Inside Diameter:** 

0.760 inches as supplied

**Distance From Intersecting Centerline Of Main Body To End Of First Branch:** 

2.900 inches after unrestricted recovery

Main Body Wall Thickness:

0.120 inches after unrestricted recovery

**First Branch Wall Thickness:** 

0.070 inches after unrestricted recovery

**Second Branch Wall Thickness:** 

0.070 inches after unrestricted recovery

**Third Branch Wall Thickness:** 

0.070 inches after unrestricted recovery

**Distance From Edge Of Main Body To Intersecting Centerlines:** 

2.420 inches after unrestricted recovery

Main Bodylength:

5.320 inches after unrestricted recovery

Angle Between Main Body And First Branch Centerlines In Deg:

30.0 after unrestricted recovery

**End Application:** 

An/aaq-19cabl

Markings:

None indicated

**Product Name:** 

Af: transition; cage: transition, 1 to 3 entry

**Special Features:** 

Material: raychem rt-1312 fluroelastomer

Flexibility:

Flexible

Color:

Black

Material:

Plastic, polyvinylidene fluoride

Material:

Plastic polyvinylidene fluoride

## NSN 5970-01-597-5011

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Styl	e Desi	ignator:
------	--------	----------

Transition-1 to 3 cables

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A22500