## NSN 5970-01-607-1313



Electrical Insulation Sleeving - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5970-01-607-1313 **Dielectric Withstanding Voltage In Volts:** 500.0 **Reliability Indicator:** Not established **Overall Length:** 4.0 feet **Tempurature Rating:** -55.0 degrees celsius and 135.0 degrees celsius **Environmental Protection:** Flame resistant and water resistant **Expanded Inside Diameter:** 1.000 inches **Recovered Inside Diameter:** 0.500 inches **Recovered Wall Thickness:** 0.035 inches **Heat Shrinkage Rating In Percent:** 50.0 **End Application:** Threat emitter **Design Form:** Full round Min. Tensile Strength (psi): 1500 pounds per square inch **Product Name:** Heat shrinkable insulation **Special Features:** Lowest shrink temperature is 90 degrees celcius. This is fungus resistant. The ultimate elongation is 200 percent. The longitudinal shrinkage is a minus 5 percent. Flexibility: Flexible Color: Blue Material: Plastic, polyolefin irradiated **Style Designator:** 

Demilitarization:

**Unit Of Measure:** 

Shrinkable
Shelf Life:

N/a

No

## NSN 5970-01-607-1313

Electrical Insulation Sleeving - Page 2 of 2



Fiig:

A22500