Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-607-2126
Dielectric Withstanding Voltage In Volts:
500.0
Reliability Indicator:
Not established
Overall Length:
4.0 feet
Tempurature Rating:
-55.0 degrees celsius and 135.0 degrees celsius
Environmental Protection:
Flame resistant and water resistant
Expanded Inside Diameter:
0.500 inches
Recovered Inside Diameter:
0.250 inches
Recovered Wall Thickness:
0.025 inches
Heat Shrinkage Rating In Percent:
50.0
End Application:
Threat emitter
Design Form:
Full round
Min. Tensile Strength (psi):
1500 pounds per square inch
Product Name:
Heat shrinkable insulation
Special Features:
Lowest shrink temperature is 90 degrees celcius. This is fungus resistant. The ultimate elongation is 200 percent. The longitudinal shrinkage
is a minus 5 percent.
Flexibility:
Flexible
Color:
Blue
Material:
Plastic, polyolefin irradiated
Style Designator:
Shrinkable
Shelf Life:
Unit Of Measure:
 Demilitarization
Demilitarization:
No

NSN 5970-01-607-2126

Electrical Insulation Sleeving - Page 2 of 2

Fiig: A22500

