

View Online at <https://aerobasegroup.com/nsn/5970-01-612-9649>

**Reliability Indicator:**

Not established

**Overall Length:**

1.50 inches

**Temperature Rating:**

-55.0 degrees celsius and 135.0 degrees celsius

**Environmental Protection:**

Flame resistant and mildew resistant

**Expanded Inside Diameter:**

0.250 inches

**Recovered Inside Diameter:**

0.125 inches

**Recovered Wall Thickness:**

Between 0.022 inches and 0.028 inches

**Heat Shrinkage Rating In Percent:**

50.0

**Design Form:**

Full round

**Markings:**

Marked iaw ams-dtl-23053

**Min. Tensile Strength (psi):**

1500 pounds per square inch

**Product Name:**

Insulation sleeving, heat shrinkable

**Flexibility:**

Flexible

**Color:**

Red

**Material:**

Plastic, polyolefin, mil-i-23053/5, class 1

**Material:**

Plastic cross-linked polyolefin

**Style Designator:**

Shrinkable

**Dielectric Material Voltage Rating Per Unit Thickness:**

500.0 volts per military /0.001 inch/

**Specification Data:**

81343-sae-ams-dtl-23053/5 national std/spec

**Specification Or Standard:**

2 color

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A22500