## NSN 5970-01-612-9649

Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-612-9649 **Reliability Indicator:** Not established **Overall Length:** 1.50 inches **Tempurature Rating:** -55.0 degrees celsius and 135.0 degrees celsius **Environmental Protection:** Flame resistant and mildew resistant **Expanded Inside Diameter:** 0.250 inches **Recovered Inside Diameter:** 0.125 inches **Recovered Wall Thickness:** Between 0.022 inches and 0.028 inches **Heat Shrinkage Rating In Percent:** 50.0 **Design Form:** Full round Markings: Marked iaw ams-dtl-23053 Min. Tensile Strength (psi): 1500 pounds per square inch **Product Name:** Insulation sleeving, heat shrinkable Flexibility: Flexible Color: Red Material: Plastic, polyolefin, mil-i-23053/5, class 1 Material: Plastic cross-linked polyolefin **Style Designator:** Shrinkable **Dielectric Material Voltage Rating Per Unit Thickness:** 500.0 volts per military /0.001 inch/ **Specification Data:** 81343-sae-ams-dtl-23053/5 national std/spec **Specification Or Standard:** 2 color

Shelf Life: N/a

## NSN 5970-01-612-9649

Electrical Insulation Sleeving - Page 2 of 2



	• •				
In	18	<i>(</i> )+	МА	261	ıre:

--

Demilitarization:

No

Fiig:

A22500