Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-617-1092

| Reliability Indicator:    |                       |  |
|---------------------------|-----------------------|--|
| Established               |                       |  |
| Tempurature Rating:       |                       |  |
| -55.0 degrees celsius and | 135.0 degrees celsius |  |
| Expanded Inside Diame     | ter:                  |  |
| 1.00 inches               |                       |  |
| Recovered Inside Diam     | eter:                 |  |
| 0.333 inches              |                       |  |
| Recovered Wall Thickn     | ess:                  |  |
| Between 0.022 inches ar   | d 0.028 inches        |  |
| End Application:          |                       |  |
| Mrap-cougar               |                       |  |
| Design Form:              |                       |  |
| Split round               |                       |  |
| Product Name:             |                       |  |
| Heat shrink/cable marker  | 3                     |  |
| Special Features:         |                       |  |
| Shrink ratio: 3: 1;       |                       |  |
| Flexibility:              |                       |  |
| Flexible                  |                       |  |
| Color:                    |                       |  |
| Red                       |                       |  |
| Material:                 |                       |  |
| Plastic polyolefin        |                       |  |
| Style Designator:         |                       |  |
| Shrinkable                |                       |  |
| Shelf Life:               |                       |  |
| N/a                       |                       |  |
| Unit Of Measure:          |                       |  |
|                           |                       |  |
| Demilitarization:         |                       |  |
| No                        |                       |  |
| Fiig:                     |                       |  |
| A22500                    |                       |  |