NSN 5970-01-617-1094

Special Purpose Electrical Insulation Sleeving - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5970-01-617-1094

Tam	nuratuu	re Rating:	
rem	buratur	re Katinu.	

-55.0 degrees celsius and 105.0 degrees celsius

Main Body Inside Diameter:

0.45 inches and 0.90 inches after unrestricted recovery

First Branch Inside Diameter:

0.20 inches and 0.40 inches after unrestricted recovery

Second Branch Inside Diameter:

0.20 inches and 0.40 inches after unrestricted recovery

Distance From Intersecting Centerline Of Main Body To End Of First Branch:

2.48 inches after unrestricted recovery

Main Body Wall Thickness:

0.04 inches after unrestricted recovery

First Branch Wall Thickness:

0.04 inches after unrestricted recovery

Second Branch Wall Thickness:

0.04 inches after unrestricted recovery

Distance From Edge Of Main Body To Intersecting Centerlines:

2.48 inches after unrestricted recovery

End Application:

Mrap-cougar

Features Provided:

Adhesive coating

Special Features:

Material: polymer blend flexible elastomeric (epb)

Flexibility:

Flexible

Color:

Black

Style Designator:

Transition-y

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500