NSN 5970-01-625-9000

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-625-9000					
Reliability Indicator:					
Not established					
Tempurature Rating:					
-55.0 degrees celsius and 150.0 degrees celsius					
Large End Wall Thickness Of Main Body:					
0.04 inches after unrestricted recovery					
Small End Wall Thickness Of Main Body:					
0.04 inches after unrestricted recovery					
Main Body Inside Diameter:					
1.20 inches as supplied					
First Branch Inside Diameter:					
0.90 inches as supplied					
Second Branch Inside Diameter:					
0.60 inches as supplied					
Distance From Intersecting Centerline Of Main Body To End Of Second Branch:					
2.48 inches after unrestricted recovery					
Distance From Intersecting Centerline Of Main Body To End Of First Branch:					
2.48 inches after unrestricted recovery					
Main Body Wall Thickness:					
0.04 inches after unrestricted recovery					
First Branch Wall Thickness:					
0.04 inches after unrestricted recovery					
Second Branch Wall Thickness:					
0.04 inches after unrestricted recovery					
Distance From Edge Of Main Body To Intersecting Centerlines:					
2.48 inches after unrestricted recovery					
Angle Between Main Body And Second Branch Centerlines In Deg:					
2.48 after unrestricted recovery					
End Application:					
B1blrutpsadts					
Product Name:					
Insulation sleeving					
Flexibility:					
Flexible					
Color:					
Black					
Material:					
Rubber synthetic					
Style Designator:					
Transition-y					
Shelf Life:					

N/a

NSN 5970-01-625-9000

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A22500