Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-653-6894

Reliability Indicator: Not established **Environmental Protection:** Flame resistant Large End Wall Thickness Of Main Body: 1.04 millimeters and 1.56 millimeters after unrestricted recovery Small End Wall Thickness Of Main Body: 0.40 millimeters and 0.60 millimeters after unrestricted recovery **Distance From Intersecting Centerlines To Edge Of Small End:** 22.5 millimeters and 27.5 millimeters after unrestricted recovery Distance From Centerline Of Small End To Edge Of Large End: 17.1 millimeters and 20.9 millimeters after unrestricted recovery Main Body Small End Inside Diameter: 5.6 millimeters and 14.0 millimeters after unrestricted recovery Main Body Large End Inside Diameter: 10.4 millimeters and 24.0 millimeters after unrestricted recovery Distance From Top Of Shoulder To Small End Of Main Body: 12.8 millimeters and 19.2 millimeters after unrestricted recovery Angle Between Large End And Small End Centerlines In Deg: 90.0 after unrestricted recovery **End Application:** 5895-01-577-3173 **Features Provided:** Adhesive coating **Product Name:** Cable boot; wire boot **Special Features:** Conforms to iso recommendations Flexibility: Flexible Height: 22.5 millimeters and 27.5 millimeters after unrestricted recovery Color: Black Material: Plastic polyolefin **Material Specification:** Rw-2058 mfr ref single material response Style Designator: Boot-90 degrees **Specification Data:** 06090-222k1**-100 manufacturers specification control

NSN 5970-01-653-6894

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A22500