NSN 5970-01-653-6894

Special Purpose Electrical Insulation Sleeving - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5970-01-653-6894

Reliability Indicator:

Not established

Environmental Protection:

Flame resistant

Large End Wall Thickness Of Main Body:

1.04 millimeters and 1.56 millimeters after unrestricted recovery

Small End Wall Thickness Of Main Body:

0.40 millimeters and 0.60 millimeters after unrestricted recovery

Distance From Intersecting Centerlines To Edge Of Small End:

22.5 millimeters and 27.5 millimeters after unrestricted recovery

Distance From Centerline Of Small End To Edge Of Large End:

17.1 millimeters and 20.9 millimeters after unrestricted recovery

Main Body Small End Inside Diameter:

5.6 millimeters and 14.0 millimeters after unrestricted recovery

Main Body Large End Inside Diameter:

10.4 millimeters and 24.0 millimeters after unrestricted recovery

Distance From Top Of Shoulder To Small End Of Main Body:

12.8 millimeters and 19.2 millimeters after unrestricted recovery

Angle Between Large End And Small End Centerlines In Deg:

90.0 after unrestricted recovery

End Application:

5895-01-577-3173

Features Provided:

Adhesive coating

Product Name:

Cable boot; wire boot

Special Features:

Conforms to iso recommendations

Flexibility:

Flexible

Height:

22.5 millimeters and 27.5 millimeters after unrestricted recovery

Color:

Black

Material:

Plastic polyolefin

Material Specification:

Rw-2058 mfr ref single material response

Style Designator:

Boot-90 degrees

Specification Data:

06090-222k1**-100 manufacturers specification control

NSN 5970-01-653-6894

Special Purpose Electrical Insulation Sleeving - Page 2 of 2



Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig: A22500