NSN 5975-00-220-2276

Stuffing Tube - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5975-00-220-2276

Thread Class:
2b second end
Thread Direction:
Right-hand both ends
Thread Length:
0.765 inches first end
Counterbore Diameter:
Between 1.250 inches and 1.310 inches
Overall Length:
8.156 inches
Item Accommodated Maximum Thickness:
5.000 inches
Bore Diameter:
Between 0.695 inches and 0.700 inches
Body Outside Diameter:
Between 2.370 inches and 2.375 inches
Overall Outside Diameter:
3.375 inches
Bore Length:
5.065 inches
First End Chamfer Depth:
0.093 inches
Thread Relief Length:
0.172 inches
Thread Relief Depth:
0.028 inches
Inside Recess Length:
0.219 inches
First Packing Chamber Inside Diameter:
Between 0.835 inches and 0.840 inches
First Packing Chamber Length:
0.188 inches
Packing Chamber Quantity:
1
First End Counterbore Diameter:
0.625 inches
Second End Counterbore Diameter:
1.500 inches
Mounting Method:
Flange and lock nuts
Thready Qty Per Inch (tpi):
18 first end

NSN 5975-00-220-2276

Stuffing Tube - Page 2 of 2



Thread Size:
2.375 inches second end
Second End Chamfer Angle:
20.0 degrees
Material:
Nickel alloy
Style Designator:
Internal-external-double
Thread Series Designator:
Uns both ends
Reference Number Differentiating Characteristics:
As differentiated and amended by spcc specification 5975-00-2202276 for sub safe items
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A049a0