

View Online at <https://aerobasegroup.com/nsn/5975-00-877-6955>

Thread Class:

2a second end

Thread Direction:

Right-hand both ends

Thread Length:

0.625 inches first end

Counterbore Diameter:

Between 0.871 inches and 0.879 inches

Counterbore Depth:

0.312 inches

Slot Depth:

Between 0.089 inches and 0.097 inches

Furnished Items:

Cap

Slot Width:

Between 0.246 inches and 0.254 inches

Slot Length:

0.312 inches

Overall Length:

1.500 inches

Item Accommodated Maximum Thickness:

0.750 inches

Bore Diameter:

Between 0.683 inches and 0.691 inches

Overall Outside Diameter:

1.625 inches

Bore Length:

Between 0.434 inches and 0.442 inches

First End Chamfer Depth:

Between 0.309 inches and 0.317 inches

Mounting End Length:

0.761 inches

First Packing Chamber Inside Diameter:

Between 0.761 inches and 0.769 inches

First Packing Chamber Length:

Between 0.746 inches and 0.754 inches

Packing Chamber Quantity:

1

Mounting Method:

Thread

Size:

0.687 inches

Thready Qty Per Inch (tpi):

12 first end

Thread Size:

1.000 inches first end

First End Chamfer Angle:

10.0 degrees

Slot Angle:

45.0 degrees

Material:

Plastic polyamide

Style Designator:

Slotted-double

Supplementary Features:

End item strategic weapons systems (poseidon and trident)

Thread Series Designator:

Un second end

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A049a0