NSN 5975-00-877-6955



Stuffing Tube - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5975-00-877-6955 **Thread Class:** 2a second end **Thread Direction:** Right-hand both ends Thread Length: 0.625 inches first end **Counterbore Diameter:** Between 0.871 inches and 0.879 inches **Counterbore Depth:** 0.312 inches **Slot Depth:** Between 0.089 inches and 0.097 inches **Furnished Items:** Cap **Slot Width:** Between 0.246 inches and 0.254 inches Slot Length: 0.312 inches **Overall Length:** 1.500 inches **Item Accommodated Maximum Thickness:** 0.750 inches **Bore Diameter:** Between 0.683 inches and 0.691 inches **Overall Outside Diameter:** 1.625 inches Bore Length: Between 0.434 inches and 0.442 inches First End Chamfer Depth: Between 0.309 inches and 0.317 inches **Mounting End Length:** 0.761 inches First Packing Chamber Inside Diameter: Between 0.761 inches and 0.769 inches First Packing Chamber Length: Between 0.746 inches and 0.754 inches **Packing Chamber Quantity:** 1 **Mounting Method:** Thread

Size:

0.687 inches

NSN 5975-00-877-6955

Stuffing Tube - Page 2 of 2



Thready Qty Per Inch (tpi):
12 first end
Thread Size:
1.000 inches first end
First End Chamfer Angle:
10.0 degrees
Slot Angle:
45.0 degrees
Material:
Plastic polyamide
Style Designator:
Slotted-double
Supplementary Features:
End item strategic weapons systems (poseidon and trident)
Thread Series Designator:
Un second end
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A049a0