NSN 5975-01-068-1899

Electrical Nonmetallic Conduit Assembly - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5975-01-068-1899

Round knurled both ends Body Outside Diameter: 0.780 inches Body Inside Diameter: 0.570 inches Terminal End Type: Plain ferrule w/coupling nut both ends Measuring Method And Length: 68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts accept the 1900-32unf screws ac	
0.780 inches Body Inside Diameter: 0.570 inches Terminal End Type: Plain ferrule w/coupling nut both ends Measuring Method And Length: 68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts the locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws; the locknuts the locknuts the locknuts the locknuts to accept the 1900-32unf screws; the locknuts the locknu	
Body Inside Diameter: 0.570 inches Terminal End Type: Plain ferrule w/coupling nut both ends Measuring Method And Length: 68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws and	
0.570 inches Terminal End Type: Plain ferrule w/coupling nut both ends Measuring Method And Length: 68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws and 190	
Terminal End Type: Plain ferrule w/coupling nut both ends Measuring Method And Length: 68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts the 1900-32unf screws and 1900-3	
Plain ferrule w/coupling nut both ends Measuring Method And Length: 68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the lo	
Measuring Method And Length: 68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws.	
68.250 inches Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws.	
Special Features: Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws; the locknuts to accept the 1900-32unf screws.	
Each assembly shall be provided with 12 no. 1900-32unf screws and 12 locknuts to accept the 1900-32unf screws; the lo	
mechanically retained to split ring	cknuts will be
Flexibility:	
Flexible	
Material:	
Plastic polytetrafluoroethylene body	
Surface Treatment:	
Nickel complete end fitting	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A02700	