## NSN 5975-01-093-1580

Conduit Outlet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5975-01-093-1580

| Hazardous Locations/environmental Protection:          |
|--|
|  |
| Explosion proof nec cl.l, gp.Cd; cl.li, gp.Efg; cl.lii |
| Conduit Trade Size Accommodated:                       |
| 0.750 inches d entrance                                |
| Overall Diameter:                                      |
| 4.625 inches   |
| Depth:   |
| 3.938 inches   |
| Conduit Entrance Type:                                 |
| Hub drilled and tapped e entrance                      |
| Conduit Type Accommodated:                             |
| Rigid metallic thickwall all entrance                  |
| Cover Mounting Method:                                 |
| Threaded fastener                                      |
| Cover Mounting Hole Quantity:                          |
| 4  |
| Cover Mounting Hole Arrangement Style:                 |
| Circular   |
| Cover Mounting Surface Type:                           |
| Flat   |
| Mounting Method:                                       |
| Lug w/hole   |
| Material:  |
| Iron, malleable  |
| Material:  |
| Iron malleable   |
| Surface Treatment:                                     |
| Cadmium and zinc                                       |
| Style Designator:                                      |
| Round no. 16 5 entrances                               |
| Surface Treatment:                                     |
| Lacquer, aluminum cellulose and cadmium and zinc       |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:                                       |
|  |
| Demilitarization:                                      |
| No   |
| Fiig:  |
| · ··ʊ·   |

A03500