

View Online at https://aerobasegroup.com/nsn/5975-01-108-8976

| Mounting Provision: | |
|---|--------------|
| Unthreaded hole | |
| Overall Depth: | |
| 17.440 inches | |
| Overall Height: | |
| 11.350 inches | |
| Overall Width: | |
| 5.340 inches | |
| Center To Center Distance Between Mounting Holes Along Width | : |
| 4.220 inches | |
| Vibration Mount Type: | |
| Сир | |
| Center To Center Distance Between Mounting Holes Along Depth | 12 |
| 15.110 inches | |
| Component Mounting Facility Type And Quantity: | |
| 2 thumbscrew | |
| Maximum Weight Capacity: | |
| 18.0 pounds | |
| Vibration Mount Load Rating Range: | |
| +2.0/+4.0 pounds | |
| Color: | |
| Aluminum | |
| Material: | |
| Aluminum | |
| Material Specification: | |
| Qq-a-250/8, temp h32 federal specification single material response | |
| Surface Treatment: | |
| Anodize | |
| Surface Treatment Specification: | |
| Mil-c-5541, type ii, grade c, class 3 military specification single treatme | ent response |
| Style Designator: | |
| Tray type w/chassis | |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Filg: | |
| A05500 | |
| Mil-std (military Standard): | |
| Mil-c-5541 spec. | |
| | |