Conduit Outlet - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5975-01-189-2103

Not rated Overall Depth: 2.750 inches Overall Length: 7.750 inches Overall Width: 3.438 inches Conduit Trade Size Accommodated: 1.500 inches all entrance Cover Opening Length: 6.000 inches Cover Opening Width: 2.250 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Colong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: Na	NI-	at rated
2.750 inches Overall Length: 7.750 inches Overall Width: 3.438 inches Conduit Trade Size Accommodated: 1.500 inches all entrance Cover Opening Length: 6.000 inches Cover Opening Width: 2.250 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: Li series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Sheff Life: Na Unit Of Measure:  Demilitarization: No		
Overall Length:         7.750 inches         Overall Width:         3.438 inches         Conduit Trade Size Accommodated:         1.500 inches all entrance         Cover Opening Length:         6.000 inches         Cover Opening Width:         2.250 inches         Conduit Entrance Type:         Hub drilled and tapped all entrance         Conduit Type Accommodated:         Rigid metallic thickwall all entrance         Conduit Type Accommodated:         Rigid metallic thickwall all entrance         Trade Designation:         Li series mark 9         Cover Mounting Method:         Self-retaining fastener         Cover Mounting Surface Type:         Flat         Material:         Aluminum, copper free         Material:         Aluminum, copper free         Style Designator:         Oblong         Surface Treatment:         Lacquer, aluminum cellulose         Sheff Life:         N/a         Unit Of Measure:            Demilitarization:		-
7.750 inches Overall Width: 3.438 inches Conduit Trade Size Accommodated: 1.500 inches all entrance Cover Opening Length: 6.000 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Style Designator: Dolong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: Na Unit Of Measure: Demilitarization: No		
Overall Width:         3.438 inches         Conduit Trade Size Accommodated:         1.500 inches all entrance         Cover Opening Length:         6.000 inches         Cover Opening Width:         2.250 inches         Conduit Entrance Type:         Hub drilled and tapped all entrance         Conduit Type Accommodated:         Rigid metallic thickwall all entrance         Trade Designation:         Ll series mark 9         Cover Mounting Method:         Self-retaining fastener         Cover Mounting Surface Type:         Flat         Material:         Aluminum, copper free         Material:         Aluminum, copper free         Style Designator:         Oblong         Surface Treatment:         Lacquer, aluminum cellulose         Shelf Life:         Na         Unit Of Measure:            Demilitarization:         No		
3.438 inches Conduit Trade Size Accommodated: 1.500 inches all entrance Cover Opening Length: 6.000 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Sheff Life: N/a Unit Of Measure:  Demilitarization: No		
Conduit Trade Size Accommodated: 1.500 inches all entrance Cover Opening Length: 6.000 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
1.500 inches all entrance Cover Opening Length: 6.000 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No	-	
Cover Opening Length: 6.000 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
6.000 inches Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Cover Opening Width: 2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
2.250 inches Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Sheff Life: Na Unit Of Measure:  Demilitarization: No	-	
Conduit Entrance Type: Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Hub drilled and tapped all entrance Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Conduit Type Accommodated: Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Rigid metallic thickwall all entrance Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Trade Designation: LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
LI series mark 9 Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Cover Mounting Method: Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		-
Self-retaining fastener Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Cover Mounting Surface Type: Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Flat Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Material: Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Aluminum, copper free Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Material: Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Aluminum, copper free Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Style Designator: Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Oblong Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure: Demilitarization: No		
Surface Treatment: Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
Lacquer, aluminum cellulose Shelf Life: N/a Unit Of Measure:  Demilitarization: No		-
Shelf Life: N/a Unit Of Measure:  Demilitarization: No		
N/a Unit Of Measure:  Demilitarization: No		-
Unit Of Measure:  Demilitarization: No		
 Demilitarization: No		
Νο	Uı	nit Of Measure:
Νο		
	De	emilitarization:
Fiig:		
	Fi	ig: