NSN 5975-01-210-8097

Electrical Nonmetallic Conduit Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5975-01-210-8097 **Thread Class:** 2b both ends **Gripping Accommodation Type:** Round knurled both ends **Hazardous Locations/environmental Protection:** Corrosion resistant **Braided Metallic Shield Type:** Tinned copper wire **Minimum Inside Bending Radius:** 1.500 inches **Body Outside Diameter:** 0.740 inches **Body Inside Diameter:** 0.438 inches **Thread Size:** 1.625 inches 2nd end **Terminal End Type:** Plain ferrule w/coupling nut both ends **Measuring Method And Length:** 13.500 inches **Special Features:** Ground wire included Flexibility: Flexible Material: Stainless steel chafing sleeve **Material Specification:** Qq-s-763 federal specification single material response chafing sleeve **Surface Treatment:** Chromate complete end fitting **Surface Treatment Specification:** Qq-p-416, type ii, class 3 federal specification single treatment response complete end fitting **Thread Series Designator:** Unef both ends Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig:

A02700

NSN 5975-01-210-8097

Electrical Nonmetallic Conduit Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-t-81914 spec.