

View Online at <https://aerobasegroup.com/nsn/5975-01-211-4415>

**Thread Class:**

2b both ends

**Gripping Accommodation Type:**

Round knurled both ends

**Hazardous Locations/environmental Protection:**

Corrosion resistant

**Braided Metallic Shield Type:**

Tinned copper wire

**Minimum Inside Bending Radius:**

2.000 inches

**Body Outside Diameter:**

0.950 inches

**Body Inside Diameter:**

0.625 inches

**Thread Size:**

1.625 inches 2nd end

**Terminal End Type:**

Plain ferrule w/coupling nut both ends

**Measuring Method And Length:**

6.000 inches working

**Special Features:**

Ground wire included

**Flexibility:**

Flexible

**Material:**

Stainless steel chafing sleeve

**Material Specification:**

Qq-s-763 federal specification single material response chafing sleeve

**Surface Treatment:**

Chromate complete end fitting

**Surface Treatment Specification:**

Qq-p-416, type ii, class 3 federal specification single treatment response complete end fitting

**Thread Series Designator:**

Unef both ends

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A02700

**Mil-std (military Standard):**

Mil-t-81914 spec.