

View Online at https://aerobasegroup.com/nsn/5975-01-214-8508

# Thread Class:

2b both ends

Gripping Accommodation Type:

Round knurled both ends

# Hazardous Locations/environmental Protection:

Corrosion resistant

### **Braided Metallic Shield Type:**

Tinned copper wire

### Minimum Inside Bending Radius:

1.000 inches

### **Body Outside Diameter:**

0.610 inches

**Body Inside Diameter:** 

# 0.281 inches

**Thread Size:** 

0.562 inches both ends

### **Terminal End Type:**

Plain ferrule w/coupling nut both ends

### Measuring Method And Length:

10.000 inches working

## **Special Features:**

Ground wire included

## Flexibility:

Flexible

Material:

Stainless steel chafing sleeve

### **Material Specification:**

Qq-s-763 federal specification single material response chafing sleeve

### Surface Treatment:

Chromate complete end fitting

### Surface Treatment Specification:

Qq-p-416, type ii, class 3 federal specification single treatment response complete end fitting

### Thread Series Designator:

Unef both ends

#### Shelf Life:

N/a

### Unit Of Measure:

---

#### Demilitarization:

Yes - demil/mli

## Fiig:

A02700



Mil-std (military Standard):

Mil-t-81914 spec.