NSN 5975-01-222-2082

Electrical Nonmetallic Conduit Assembly - Page 1 of 2



Licethical Nonlinetalile Conduit / 1836 hibly in age in or 2
View Online at https://aerobasegroup.com/nsn/5975-01-222-2082
Thread Class:
2b both ends
Gripping Accommodation Type:
Round knurled both ends
Hazardous Locations/environmental Protection:
Corrosion resistant
Braided Metallic Shield Type:
Tinned copper wire
Minimum Inside Bending Radius:
2.130 inches
Body Outside Diameter:
1.100 inches
Body Inside Diameter:
0.750 inches
Thread Size:
1.062 inches both ends
Terminal End Type:
Plain ferrule w/coupling nut both ends
Measuring Method And Length:
12.000 inches working
Special Features:
Ground wire included
Flexibility:
Flexible
Material:
Stainless steel chafing sleeve
Material Specification:
Qq-s-763 federal specification single material response chafing sleeve
Surface Treatment:
Chromate complete end fitting
Surface Treatment Specification:
Qq-p-416, type ii, class 3 federal specification single treatment response complete end fitting
Thread Series Designator:
Unef both ends
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No

Fiig:

A02700

NSN 5975-01-222-2082

Electrical Nonmetallic Conduit Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-t-81914 spec.