NSN 5975-01-228-9530

Electrical Nonmetallic Conduit Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5975-01-228-9530 **Thread Class:** 2b both ends **Gripping Accommodation Type:** Round knurled both ends **Hazardous Locations/environmental Protection:** Corrosion resistant **Braided Metallic Shield Type:** Tinned copper wire **Minimum Inside Bending Radius:** 2.130 inches **Body Outside Diameter:** 1.100 inches **Body Inside Diameter:** 0.750 inches **Thread Size:** 1.312 inches 1st end **Terminal End Type:** Plain ferrule w/coupling nut both ends **Measuring Method And Length:** 12.000 inches working **Special Features:** With ground wire Flexibility: Flexible Material: Stainless steel chafing sleeve **Material Specification:** Qq-s-763 federal specification single material response chafing sleeve **Surface Treatment:** Chromate complete end fitting **Surface Treatment Specification:** Qq-p-416, type ii, class 3 federal specification single treatment response complete end fitting **Thread Series Designator:** Unef both ends Shelf Life: N/a **Unit Of Measure: Demilitarization:** No

Fiig: A02700

NSN 5975-01-228-9530

Electrical Nonmetallic Conduit Assembly - Page 2 of 2



Mil-std (military Standard):

Mil-t-81914 spec.