## NSN 5975-01-363-3583

Stuffing Tube - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5975-01-363-3583

| Thread Class:   |
|---|
| 2a first end  |
| Inside Diameter:  |
| Between 1.032 inches and 1.250 inches   |
| Item Accommodated Maximum Thickness:  |
| 0.375 inches  |
| Body Outside Diameter:  |
| 2.440 inches  |
| Packing Chamber Quantity:   |
| 1   |
| Width Across Flats:   |
| 2.000 inches  |
| Mounting Method:  |
| Lock nuts   |
| Thready Qty Per Inch (tpi):   |
| 18 first end  |
| Thread Size:  |
| 1.750 inches first end  |
| Special Features:   |
| Internal nut thread 1.625-18unef  |
| Material:   |
| Aluminum alloy 2011   |
| Material Specification:   |
| Qq-a-225/3 federal specification single material response   |
| Surface Treatment:  |
| Cadmium and nickel  |
| Surface Treatment Specification:  |
| Qp-p-416 federal specification 1st treatment response and mil-c-26074 military specification 2nd treatment response |
| Thread Series Designator:   |
| Uns first end   |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |
| A049a0  |
| Mil-std (military Standard):  |
| Mil-c-26074 spec.   |