NSN 5975-01-526-5363

Cable Collar - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5975-01-526-5363

Overall Length: 1.000 inches Material Thickness: 0.190 inches Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides meast mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular Shelf Life:	
Material Thickness: 0.190 inches Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides meast mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opt Material: Any acceptable body Style Designator: Annular	
Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measi mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular	
Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides meast mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular	
2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measure mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the state of the sta	
End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measure mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the state of the stat	
An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the system of the s	
Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measurementing holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the product of the pr	
Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measurementing holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular	
Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposite to the state of the state	
Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.835 at flange edge and 0.812 at opposition of the diameter is 0.835	
Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge edge and 0.812 at opposition of the diameter is 0.635. At flange edge edge edge edge edge edge edge e	
Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measure mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635 at flange edge edge edge and 0.812 at opposition of the diameter is 0.635 at flange edge edge edge ed	
mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter of th	
Material: Any acceptable body Style Designator: Annular	re 1.500; 4
Any acceptable body Style Designator: Annular	osite end
Style Designator: Annular	
Annular	
Shalf Life:	
onen Life.	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A02000	