NSN 5975-01-526-5363

Cable Collar - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5975-01-526-5363

| Overall Length: 1.000 inches Material Thickness: 0.190 inches Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measi mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular Shelf Life: | |
|--|-------------|
| Material Thickness: 0.190 inches Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides meast mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opt Material: Any acceptable body Style Designator: Annular | |
| Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measi mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular | |
| Body Outside Diameter: 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides meast mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular | |
| 2.000 inches End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measure mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the state of the sta | |
| End Application: An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measure mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the state of the stat | |
| An/wld- (v) mine hunting sys; antenna mast Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the system of the s | |
| Accommodation Hole Inside Diameter: 0.625 inches Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measurementing holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the product of the pr | |
| Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measurementing holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opp Material: Any acceptable body Style Designator: Annular | |
| Product Name: Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposite to the state of the state | |
| Cable entry flange Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.835 at flange edge and 0.812 at opposition of the diameter is 0.835 | |
| Special Features: Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measuremounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge and 0.812 at opposition of the diameter is 0.635. At flange edge edge and 0.812 at opposition of the diameter is 0.635. At flange edge edge edge edge edge edge edge e | |
| Outer diameter of flange is 2.000 inches, cut off on each side so that top and bottom arcs are 1.500 in. And vertical sides measure mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635. The diameter is 0.635 at flange edge and 0.812 at opposition of the diameter is 0.635 at flange edge edge edge and 0.812 at opposition of the diameter is 0.635 at flange edge edge edge ed | |
| mounting holes are 0.170 in. In diam, 0.168 in. Apart in both directions; inner diameter is 0.635 at flange edge and 0.812 at opposition of the diameter of th | |
| Material: Any acceptable body Style Designator: Annular | re 1.500; 4 |
| Any acceptable body Style Designator: Annular | osite end |
| Style Designator: Annular | |
| Annular | |
| | |
| Shalf Life: | |
| onen Life. | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |
| Fiig: | |
| A02000 | |