NSN 5977-00-390-3000

Electrical Contact Brush - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5977-00-390-3000

| Shunt Position Designator: | | | | | |
|--|--|--|--|--|--|
| 5 | | | | | |
| Body Style: | | | | | |
| Rectangular commutator | | | | | |
| Head Diameter: | | | | | |
| 0.296 inches | | | | | |
| Head Length: | | | | | |
| 0.125 inches | | | | | |
| Width: | | | | | |
| 0.500 inches | | | | | |
| Thickness: | | | | | |
| 0.188 inches | | | | | |
| Length: | | | | | |
| 1.000 inches | | | | | |
| Terminal Diameter: | | | | | |
| 0.375 inches | | | | | |
| Spring Free Length: | | | | | |
| 3.000 inches | | | | | |
| Largest Outside Diameter: | | | | | |
| 0.350 inches | | | | | |
| Brush Shunt Length: | | | | | |
| 2.000 inches single shunt | | | | | |
| Top Style: | | | | | |
| Cylindrical head | | | | | |
| Contact Face Style: | | | | | |
| Flat | | | | | |
| Shunt Insulation Provision And Quantity: | | | | | |
| 1 uninsulated | | | | | |
| Criticality Code Justification: | | | | | |
| Matt and mdcl | | | | | |
| Pressure Spring Type And Quantity: | | | | | |
| 1 cylindrical | | | | | |
| Material: | | | | | |
| Electrographitic | | | | | |
| Material Specification: | | | | | |
| Stackpole carbon ci, gr wa10u mfr ref single material response | | | | | |
| Style Designator: | | | | | |
| One piece | | | | | |
| Terminal Type And Quantity: | | | | | |
| 1 round cap | | | | | |
| Shelf Life: | | | | | |
| | | | | | |

N/a

NSN 5977-00-390-3000

Electrical Contact Brush - Page 2 of 2



| | • - | | | |
|----|-----|------|---------|---|
| In | ıŧ | ()t | Measure | • |
| | | | | |

--

Demilitarization:

No

Fiig:

A01500