

View Online at <https://aerobasegroup.com/nsn/5977-00-586-3659>

**Shunt Position Designator:**

2 and 8

**Peripheral Speed:**

8000 feet per minute

**Body Style:**

Rectangular commutator

**Radius:**

14.000 inches

**Width:**

1.500 inches

**Thickness:**

0.563 inches

**Length:**

2.250 inches

**Clip Length:**

0.969 inches

**Brush Shunt Length:**

4.500 inches all shunts

**Terminal Slot Width:**

0.281 inches

**Top Style:**

Beveled front

**Contact Face Style:**

Concave on bevel

**Bevel Angle:**

28.5 degrees

**Clip Type:**

Nema hammer type angular a-extended

**Shunt Insulation Provision And Quantity:**

2 uninsulated

**Angle:**

35.0 degrees

**Clip Bevel Angle In Deg:**

35.0

**Criticality Code Justification:**

Matt and mdcl

**Material:**

Electrographitic

**Material Specification:**

Union carbide corporation grade sa45 mfr ref single material response

**Style Designator:**

One piece

**Terminal Type And Quantity:**

1 straight w/slot

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A01500