

View Online at <https://aerobasegroup.com/nsn/5977-00-646-4905>

**Shunt Position Designator:**

1212

**Peripheral Speed:**

7000 feet per minute7000 feet per minute

**Body Style:**

Rectangular commutatorrectangular commutator

**Width:**

1.250 inches 1.250 inches

**Shoulder Height:**

Any acceptable

**Shoulder Width:**

Any acceptable

**Thickness:**

0.625 inches 0.625 inches

**Length:**

1.625 inches 1.625 inches

**Brush Shunt Length:**

4.000 inches single shunt4.000 inches single shunt

**Terminal Hole Diameter:**

0.344 inches 0.344 inches

**Top Style:**

Beveled front with left shoulderbeveled front with left shoulder

**Contact Face Style:**

Beveledbeveled

**Bevel Angle:**

30.0 degrees 30.0 degrees

**Shunt Insulation Provision And Quantity:**

1 uninsulated

**Angle:**

30.0 degrees

**Material:**

Electrographitic

**Material Specification:**

Union carbide corp, carbon products div, grade sa-35 mfr ref single material response

**Style Designator:**

One piece

**Terminal Type And Quantity:**

1 straight w/slot

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A01500