NSN 5980-01-324-2431

Light Emitting Diode - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5980-01-324-2431

| Inclosure material: |
|----------------------------------------------------------------------------------------------------------------------------------------------|
| Plastic |
| Overall Length: |
| 0.255 inches |
| Terminal Length: |
| 0.190 inches |
| Overall Height: |
| 0.099 inches |
| Overall Width: |
| 0.108 inches |
| Lens Transparency: |
| Transparent |
| Function For Which Designed: |
| Visible light emitting |
| Internal Configuration: |
| Point contact |
| Internal Junction Configuration: |
| Pn |
| Mounting Method: |
| Terminal |
| Features Provided: |
| Quality assurance level tx |
| Semiconductor Material: |
| Gallium arsenide phosphide |
| Voltage Rating In Volts Per Characteristic: |
| 25.0 forward voltage, dc |
| Current Rating Per Characteristic: |
| 7.50 milliamperes source cutoff current preset |
| Power Rating Per Characteristic: |
| 225.0 milliwatts small-signal input power, common-collector preset |
| Color Tone Produced Per Source: |
| Green lens |
| Luminous Intensity: |
| 0.5 millicandela |
| Maximum Operating Tempurature Per Measurement Point: |
| 100.0 degrees celsius ambient air |
| Test Data Document: |
| 81349-mil-s-19500 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 2 uninsulated wire lead |
| Specification Data: |

81349-mil-s-19500/574 government specification

NSN 5980-01-324-2431

Light Emitting Diode - Page 2 of 2



Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A110a0