NSN 5980-01-331-3188

Light Emitting Diode - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5980-01-331-3188

Metal and plastic Overall Length: 1.437 inches Overall Diameter: 0.360 inches Lens Transparency: Transparent Function For Which Designed: Visible light emitting End Application: Tactical air operations module an/tyq-2 (v) 1 Mounting Facility Quantity: 1 for Application: Threaded stud Threaded stud Thread Size: 0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 5.00 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shief Life: N/a	
Overall Diameter:1.437 inchesOverall Diameter:0.360 inchesLens Transparency:TransparentFunction For Which Designed:Visible light emittingEnd Application:Tactical air operations module an/tyq-2 (v) 1Mounting Facility Quantity:1Mounting Method:Thread State:0.250 inchesVoltage Rating In Volts Per Characteristic:5.0 forward voltage, dcCurrent Rating Per Characteristic:15.00 milliamperes all primaries presetColor Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Vire wrap finish goldPrecious Material:GoldThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:Na	Inclosure Material:
1.437 inchesOverall Diameter:0.360 inchesLens Transparency:TransparentFunction For Which Designed:Visible light emittingEnd Application:Tactical air operations module an/tyq-2 (v) 1Mounting Facility Quantity:1Mounting Method:Threaded studThreaded studCurrent Rating In Volts Per Characteristic:5.0 fonward voltage, dcCurrent Rating Per Characteristic:15.00 milliamperes all primaries presetColor Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious MaterialCondThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	Metal and plastic
Overall Diameter:0.360 inchesLens Transparency:TransparentFunction For Which Designed:Visible light emittingEnd Application:Tactical air operations module an/tyq-2 (v) 1Mounting Facility Quantity:1Mounting Method:Threaded studThreaded studColor once Source:Voltage Rating In Volts Per Characteristic:5.0 forward voltage, dcColor Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material:Moire and Erice:OldThread Series Designator:UnfCurrent Rating Per Characterist:SolderSpecial Features:Emi shieldingPrecious Material:ColorYere wrap finish goldPrecious Material:ColdShiel Life:N/a	Overall Length:
0.360 inches Lens Transparency: Transparent Function For Which Designed: Visible light emitting End Application: Tactical air operations module an/tyq-2 (v) 1 Mounting Facility Quantity: 1 Mounting Method: Threaded stud Thread Size: 0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: N/a	1.437 inches
Lens Transparent Function For Which Designed: Visible light emitting End Application: Tactical air operations module an/tyq-2 (v) 1 Mounting Facility Quantity: 1 Mounting Method: Threaded stud Thread Size: 0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Overall Diameter:
TransparentFunction For Which Designed:Visible light emittingEnd Application:Tactical air operations module an/tyq-2 (v) 1Mounting Facility Quantity:1Mounting Method:Threaded studThread Size:0.250 inchesVoltage Rating In Volts Per Characteristic:5.0 forward voltage, dcCurrent Rating Per Characteristic:15.00 milliamperes all primaries presetColor Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious MaterialColdThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	0.360 inches
Function For Which Designed:Visible light emittingEnd Application:Tactical air operations module an/tyq-2 (v) 1Mounting Facility Quantity:1Mounting Method:Threaded studThreaded studThread Size:0.250 inchesVoltage Rating In Volts Per Characteristic:5.0 forward voltage, dcCurrent Rating Per Characteristic:15.00 milliamperes all primaries presetColor Tone Produced Per Source:Yellow lensMaxinum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious Material:GoldThread Series Designator:UnfYenrinal Type And Quantity:2 wire wrapShelf Life:N/a	Lens Transparency:
Visible light emitting End Application: Tactical air operations module an/tyq-2 (v) 1 Mounting Facility Quantity: 1 Mounting Method: Threaded stud Threaded stud Thread Size: 0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Vire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Transparent
End Application:Tactical air operations module an/tyq-2 (v) 1Mounting Facility Quantity:1Mounting Method:Threaded studThread Size:0.250 inchesVoltage Rating In Volts Per Characteristic:5.0 forward voltage, dcCurrent Rating Per Characteristic:15.00 milliamperes all primaries presetColor Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Erni shieldingPrecious Material And Location:Wire wrap finish goldPrecious Material:GoldThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	Function For Which Designed:
Tactical air operations module an/tyq-2 (v) 1 Mounting Facility Quantity: 1 Mounting Method: Threaded stud Threaded stud Threaded stud Thread Size: 0.250 inches Voltage Rating In Volts Per Characteristic: 0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Visible light emitting
Mounting Facility Quantity:1Mounting Method:Threaded studThread Size:0.250 inchesVoltage Rating In Volts Per Characteristic:5.0 forward voltage, dcCurrent Rating Per Characteristic:15.00 milliamperes all primaries presetColor Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious Material:GoldInfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	End Application:
1 Mounting Method: Threaded stud Thread Size: 0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Tactical air operations module an/tyq-2 (v) 1
Nounting Method: Threaded stud Thread Size: 0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Mounting Facility Quantity:
Threaded stud Thread Size: O.250 inches Voltage Rating In Volts Per Characteristic: S.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	1
Thread Size:0.250 inchesVoltage Rating In Volts Per Characteristic:5.0 forward voltage, dcCurrent Rating Per Characteristic:15.00 milliamperes all primaries presetColor Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious Material:GoldThread Series Designator:UnfShelf Life:N/a	Mounting Method:
0.250 inches Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap	Threaded stud
Voltage Rating In Volts Per Characteristic: 5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Thread Size:
5.0 forward voltage, dc Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	0.250 inches
Current Rating Per Characteristic: 15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Voltage Rating In Volts Per Characteristic:
15.00 milliamperes all primaries preset Color Tone Produced Per Source: Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life:	5.0 forward voltage, dc
Color Tone Produced Per Source:Yellow lensMaximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious Material:GoldThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	Current Rating Per Characteristic:
Yellow lens Maximum Operating Tempurature Per Measurement Point: 95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	15.00 milliamperes all primaries preset
Maximum Operating Tempurature Per Measurement Point:95.0 degrees celsius junctionSpecial Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious Material:GoldThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	Color Tone Produced Per Source:
95.0 degrees celsius junction Special Features: Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Yellow lens
Special Features:Emi shieldingPrecious Material And Location:Wire wrap finish goldPrecious Material:GoldThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	Maximum Operating Tempurature Per Measurement Point:
Emi shielding Precious Material And Location: Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	95.0 degrees celsius junction
Precious Material And Location:Wire wrap finish goldPrecious Material:GoldThread Series Designator:UnfTerminal Type And Quantity:2 wire wrapShelf Life:N/a	Special Features:
Wire wrap finish gold Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Emi shielding
Precious Material: Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Precious Material And Location:
Gold Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Wire wrap finish gold
Thread Series Designator: Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Precious Material:
Unf Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Gold
Terminal Type And Quantity: 2 wire wrap Shelf Life: N/a	Thread Series Designator:
2 wire wrap Shelf Life: N/a	Unf
Shelf Life: N/a	Terminal Type And Quantity:
N/a	2 wire wrap
	Shelf Life:
Unit Of Measures	N/a
Unit Of Measure:	Unit Of Measure:
Demilitarization:	Demilitarization:
	No
	NO

NSN 5980-01-331-3188 Light Emitting Diode - Page 2 of 2

Fiig: A110a0

