NSN 5985-00-003-5343

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-003-5343

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange single connection facility

Thread Direction:

Right-hand second flange single connection facility

Flange Quantity:

2

Flange Inside Width:

0.897 inches all flanges and 0.903 inches all flanges

Flange Inside Height:

0.397 inches all flanges and 0.403 inches all flanges

Flange Outside Width:

1.610 inches all flanges and 1.640 inches all flanges

Flange Outside Height:

1.610 inches all flanges and 1.640 inches all flanges

Flange Inside Diameter:

1.000 inches all flanges and 1.006 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches first flange single connection facility and 0.172 inches first flange single connection facility

Voltage Standing Wave Ratio:

1.08

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

20.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.997 inches and 1.003 inches

Thread Size:

0.164 inches second flange single connection facility

Waveguide Inside Width:

Between 0.897 inches and 0.903 inches

Waveguide Inside Height:

Between 0.397 inches and 0.403 inches

Waveguide Outside Height:

Between 0.497 inches and 0.503 inches

Waveguide Longer Offset Distance:

2.375 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole first flange single connection facility

NSN 5985-00-003-5343 Waveguide Assembly - Page 2 of 2



Flange Style:
Choke type first flange
Waveguide Offset Distance:
1.750 inches
Flexibility:
Flexible single tubing segment
Material:
Plastic vinyl acetate single tubing jacket
Surface Treatment:
Oxide film all tubing segment and flange all surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc second flange single connection facility
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:

A073a0