NSN 5985-00-003-8794

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-003-8794

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Bend Angle In Deg:

90.0 single bend e-plane

Tubing Wall Construction Style:

Seamless single tubing segment

Tubing Twist Type:

Straight twist single tubing segment

Tubing Twist Angle In Deg:

10.0 single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches second flange

Flange Inside Height:

0.394 inches second flange

Flange Outside Width:

1.313 inches second flange

Flange Outside Height:

1.312 inches first flange

Flange Inside Diameter:

0.994 inches first flange

Flange Depth:

0.375 inches first flange

Flange Connecting Hole Diameter:

0.144 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Waveguide Outside Width:

0.702 inches

Thread Size:

0.138 inches first flange all connection facilities

Waveguide Inside Width:

0.622 inches

Waveguide Inside Height:

0.311 inches

NSN 5985-00-003-8794 Waveguide Assembly - Page 2 of 2



Waveguide Outside Height:
0.391 inches
Waveguide Longer Offset Distance:
7.156 inches
Flange Connecting Facility And Quantity:
4 unthreaded hole second flange all connection facilities
Flange Style:
Cover type second flange
Waveguide Offset Distance:
4.125 inches
Flexibility:
Flexible single tubing segment
Material:
Plastic single tubing jacket
Surface Treatment:
Any acceptable single tubing segment all surfaces
Style Designator:
Bend type
Thread Series Designator:
Unc first flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
Yes - demil/mli
Fiig:
A073a0