NSN 5985-00-004-0069

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-004-0069

Application Design:
Transmission line
Body Style:
Coaxial type
Overall Length:
5.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
4.750 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.625 inches
Overall Height:
1.500 inches
Overall Width:
3.000 inches
Unthreaded Mounting Hole Diameter:
0.199 inches
Operating Tempurature Range:
-54.0/+71.0 degrees celsius
Coaxial Connector Series Designation:
N
Power Rating:
5.0 watts average
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0 to 20.0
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:
4 unthreaded hole
Frequency Range:
Between 225.000 megahertz and 400.000 megahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Adjustment Device Type And Quantity:
1 knob
Mounting Facility Pattern:
Four position rectangular
Impedance Rating In Ohms:
50.0 input-output
Terminal Type And Quantity:

2 connector, coaxial, female and 1 connector, coaxial, male

NSN 5985-00-004-0069

Variable Attenuator - Page 2 of 2



_			•		
•	n	ο.	•	18	e:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0