NSN 5985-00-004-1062

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-004-1062

Annilastian	Design
Application	Design:

Transmission line

Body Style:

Coaxial type

Overall Length:

3.670 inches

Overall Height:

3.848 inches

Overall Width:

3.130 inches

First Flat Length:

0.300 inches

Flat Height:

0.215 inches

Shaft Diameter:

0.250 inches

Shaft Length:

1.170 inches

Distance Between Mounting Facility Centers:

1.250 inches

Operating Tempurature Range:

-0.0 to 70.0 degrees celsius

Voltage Standing Wave Ratio:

1.25

Coaxial Connector Series Designation:

Bnc

Power Rating:

400.0 milliwatts average

Mounting Facility Screw Thread Series Designator:

Unc

Insertion Loss At Minimum Attenuation In Maximum Decibels:

0.3

Overall Attenuation Range In Decibels:

+0.0/+10.0

Attenuation Accuracy Reference Frequency:

10.0 megahertz

Attenuation Variation Method:

Stepped

Step Position Quantity:

10

Attenuation Per Step In Decibels:

1.0

NSN 5985-00-004-1062

Variable Attenuator - Page 2 of 2



Mounting Facility Type And Quantity: 2 threaded hole **Frequency Range:** Between 10.000 megahertz and 500.000 megahertz **Overall Attenuation Accuracy In Decibels:** -0.60 to 0.60 Mounting Thread Quantity: 32 per inch Adjustment Device Type And Quantity: 1 shaft **Mounting Facility Pattern:** Two position in-line Shaft Type: Round, flatted Mounting Facility Screw Thread Diameter: 0.164 inches Impedance Rating In Ohms: 50.0 input-output **Terminal Type And Quantity:** 2 connector, coaxial, female Shelf Life: N/a Unit Of Measure: ---Demilitarization: Yes - demil/mli Fiig: A223a0