

View Online at <https://aerobasegroup.com/nsn/5985-00-004-6282>

**Cross Sectional Shape:**

Internal, rectangular external, rectangular

**Tubing Wall Construction Style:**

Corrugated single tubing segment

**Flange Quantity:**

2

**Flange Inside Width:**

1.253 inches all flanges and 1.256 inches all flanges

**Flange Inside Height:**

0.628 inches all flanges and 0.631 inches all flanges

**Flange Outside Width:**

1.860 inches all flanges and 1.890 inches all flanges

**Flange Outside Height:**

1.860 inches all flanges and 1.890 inches all flanges

**Flange Depth:**

0.423 inches all flanges and 0.453 inches all flanges

**Flange Connecting Hole Diameter:**

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

**Voltage Standing Wave Ratio:**

1.10

**Insertion Loss In Decibels:**

0.25

**Waveguide Outside Width:**

Between 1.246 inches and 1.254 inches

**Waveguide Inside Width:**

Between 1.118 inches and 1.126 inches

**Waveguide Inside Height:**

Between 0.493 inches and 0.501 inches

**Waveguide Outside Height:**

Between 0.621 inches and 0.629 inches

**Flange Connecting Facility And Quantity:**

4 unthreaded hole all flanges all connection facilities

**Flange Style:**

Cover type all flanges

**Waveguide Length:**

4.333 feet

**Flexibility:**

Flexible single tubing segment

**Material:**

Aluminum alloy all flange

**Precious Material And Location:**

Flange outside surface and tubing outside surface silver

**Precious Material:**

Silver

**Surface Treatment:**

Silver all tubing segment and flange outside surfaces

**Style Designator:**

Straight type

**Fsc Application Data:**

Antennas, waveguides and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A073a0