NSN 5985-00-004-7578

Fixed Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-004-7578

Application Design:
Transmission line
Body Material:
Steel, stainless
Body Style:
Round, terminal/terminals in opposite surface
Body Surface Treatment:
Any acceptable
Overall Length:
1.400 inches
Overall Diameter:
0.562 inches
Operating Tempurature Range:
-55.0/+125.0 degrees celsius
Voltage Standing Wave Ratio:
1.35
Input Impedance Rating In Ohms:
50.0
Output Impedance Rating In Ohms:
50.0
Coaxial Connector Series Designation:
Sma
Power Rating:
1.0 watts average and 1.0 kilowatts peak
Rf Signal Attenuation In Decibels:
20.0
Voltage Standing Wave Ratio Frequency Range:
+0.0/+18.0 gigahertz
Attenuation Accuracy Reference Frequency:
18.0 gigahertz
Attenuation Accuracy In Decibels:
-0.50/+0.50
Connection Type Per Function:
Connection Type Per Function: Female input and male output
Female input and male output
Female input and male output Unpackaged Unit Weight:
Female input and male output Unpackaged Unit Weight: 0.400 ounces
Female input and male output Unpackaged Unit Weight: 0.400 ounces Mounting Method:
Female input and male output Unpackaged Unit Weight: 0.400 ounces Mounting Method: Connector
Female input and male output Unpackaged Unit Weight: 0.400 ounces Mounting Method: Connector Terminal Type And Quantity:

NSN 5985-00-004-7578

Fixed Attenuator - Page 2 of 2



Fsc Application Data

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A20000