NSN 5985-00-004-9420

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-004-9420

Unable To Decode:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Unable To Decode:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange

Flange Inside Height:

1.002 inches second flange

Flange Outside Diameter:

3.610 inches second flange and 3.640 inches second flange

Flange Depth:

0.922 inches first flange and 0.953 inches first flange

Flange Connecting Hole Diameter:

0.199 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.08

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

15.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Waveguide Longer Offset Distance:

Between 11.287 inches and 11.407 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

NSN 5985-00-004-9420 Waveguide Assembly - Page 2 of 2



Waveguide Offset Distance:
Between 10.876 inches and 11.000 inches
Special Features:
Operating frequency range 5.4 to 5.9 ghz; temperature range minus 65.0 to plus 75.0 degrees $\ensuremath{\text{c}}$
Flexibility:
Flexible single tubing segment
Material:
Copper alloy single tubing segment
Precious Material And Location:
External tubing surfaces silver
Precious Material:
Silver
Surface Treatment:
Rubber single tubing segment outside surfaces and silver single tubing segment outside surfaces
Style Designator:
Bend type
Thread Series Designator:
Unf first flange all connection facilities
Specification Data:
10001-2270336 manufacturers specification control
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig:

A073a0