NSN 5985-00-005-2960

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-005-2960

Cross Sectional Shape:				
Internal, rectangular external, rectangular				
Tubing Wall Construction Style:				
Corrugated single tubing segment				
Flange Quantity:				
2				
Flange Inside Width:				
2.840 inches all flanges				
Flange Inside Height:				
1.340 inches all flanges				
Flange Outside Width:				
4.500 inches all flanges				
Flange Outside Height:				
3.000 inches all flanges				
Flange Depth:				
0.690 inches all flanges				
Flange Connecting Hole Diameter:				
0.531 inches all flanges second connection facility				
Voltage Standing Wave Ratio:				
1.05				
Insertion Loss In Decibels:				
Insertion Loss In Decibels: 0.02				
0.02				
0.02 Maximum Operating Pressure:				
0.02Maximum Operating Pressure:26.0 pounds per square inch gage				
0.02 Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width:				
0.02 Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches				
0.02 Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width:				
0.02 Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches				
0.02 Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height:				
0.02 Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches				
Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches Waveguide Outside Height:				
0.02 Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches Waveguide Outside Height: 1.500 inches				
Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches Waveguide Outside Height: 1.500 inches Flange Connecting Facility And Quantity:				
Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches Waveguide Outside Height: 1.500 inches Flange Connecting Facility And Quantity: 8 unthreaded hole all flanges second connection facility				
Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches Waveguide Outside Height: 1.500 inches Flange Connecting Facility And Quantity: 8 unthreaded hole all flanges second connection facility Flange Style:				
Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches Waveguide Outside Height: 1.500 inches Flange Connecting Facility And Quantity: 8 unthreaded hole all flanges second connection facility Flange Style: Contact type all flanges				
Maximum Operating Pressure: 26.0 pounds per square inch gage Waveguide Outside Width: 3.000 inches Waveguide Inside Width: 2.840 inches Waveguide Inside Height: 1.340 inches Waveguide Outside Height: 1.500 inches Flange Connecting Facility And Quantity: 8 unthreaded hole all flanges second connection facility Flange Style: Contact type all flanges Waveguide Length:				

Material:

Plastic single tubing jacket

NSN 5985-00-005-2960

Waveguide Assembly - Page 2 of 2



	tment:

Any acceptable all flange inside surfaces

Style Designator:

Straight type

Shelf Life:

N/a

Unit Of Measure:

__

Demilitarization:

Yes - demil/mli

Fiig:

A073a0