NSN 5985-00-005-2964

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-005-2964

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.840 inches second flange

Flange Inside Height:

1.340 inches second flange

Flange Outside Width:

4.500 inches second flange

Flange Outside Height:

3.000 inches second flange

Flange Outside Diameter:

5.313 inches first flange

Flange Depth:

0.750 inches first flange

Flange Connecting Hole Diameter:

0.257 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.02

Maximum Operating Pressure:

26.0 pounds per square inch gage

Waveguide Outside Width:

3.000 inches

Thread Size:

0.250 inches first flange all connection facilities

Waveguide Inside Width:

2.840 inches

Waveguide Inside Height:

1.340 inches

Waveguide Outside Height:

1.500 inches

Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

NSN 5985-00-005-2964 Waveguide Assembly - Page 2 of 2



Flange Style:
Contact type second flange
Waveguide Length:
7.750 inches
Flexibility:
Flexible single tubing segment
Material:
Plastic single tubing jacket
Surface Treatment:
Any acceptable all flange inside surfaces
Style Designator:
Straight type
Thread Series Designator:
Unc first flange all connection facilities
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli
Fiig:
A073a0