

View Online at <https://aerobasegroup.com/nsn/5985-00-005-2964>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2a first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.840 inches second flange

Flange Inside Height:

1.340 inches second flange

Flange Outside Width:

4.500 inches second flange

Flange Outside Height:

3.000 inches second flange

Flange Outside Diameter:

5.313 inches first flange

Flange Depth:

0.750 inches first flange

Flange Connecting Hole Diameter:

0.257 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.02

Maximum Operating Pressure:

26.0 pounds per square inch gage

Waveguide Outside Width:

3.000 inches

Thread Size:

0.250 inches first flange all connection facilities

Waveguide Inside Width:

2.840 inches

Waveguide Inside Height:

1.340 inches

Waveguide Outside Height:

1.500 inches

Flange Connecting Facility And Quantity:

8 threaded hole first flange all connection facilities

Flange Style:

Contact type second flange

Waveguide Length:

7.750 inches

Flexibility:

Flexible single tubing segment

Material:

Plastic single tubing jacket

Surface Treatment:

Any acceptable all flange inside surfaces

Style Designator:

Straight type

Thread Series Designator:

Unc first flange all connection facilities

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A073a0