NSN 5985-00-005-6834

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-005-6834

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b second flange all connection facilities

Thread Direction:

Right-hand second flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches first flange

Flange Inside Height:

0.394 inches first flange

Flange Outside Width:

1.298 inches first flange and 1.328 inches first flange

Flange Outside Height:

1.298 inches first flange and 1.328 inches first flange

Flange Inside Diameter:

0.985 inches second flange and 1.015 inches second flange

Flange Depth:

0.360 inches second flange and 0.390 inches second flange

Flange Connecting Hole Diameter:

0.169 inches first flange all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.10

Thready Qty Per Inch (tpi):

32 second flange all connection facilities

Maximum Operating Pressure:

25.0 pounds per square inch gage

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Thread Size:

0.138 inches second flange all connection facilities

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

NSN 5985-00-005-6834

Waveguide Assembly - Page 2 of 2

Yes - demil/mli

Fiig: A073a0



Flange Connecting Facility And Quantity: 4 unthreaded hole first flange all connection facilities Flange Style: Cover type first flange Waveguide Length: Between 11.980 inches and 12.020 inches **Special Features:** Silver plate brass guide per qq-s-365; temperature range minus 54 degrees c to plus 71 degrees c Flexibility: Flexible single tubing segment Material: Copper alloy single tubing segment **Precious Material And Location:** Brass guide silver **Precious Material:** Silver **Surface Treatment:** Rubber single tubing segment all surfaces **Style Designator:** Straight type **Thread Series Designator:** Unc second flange all connection facilities **Fsc Application Data:** Antennas, waveguides, and related equipment Shelf Life: N/a **Unit Of Measure: Demilitarization:**