

View Online at <https://aerobasegroup.com/nsn/5985-00-006-8999>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Corrugated single tubing segment

Tubing Twist Type:

Twistable single tubing segment

Flange Quantity:

2

Flange Inside Width:

1.253 inches all flanges and 1.256 inches all flanges

Flange Inside Height:

0.628 inches all flanges and 0.631 inches all flanges

Flange Outside Width:

1.860 inches all flanges and 1.890 inches all flanges

Flange Outside Height:

1.860 inches all flanges and 1.890 inches all flanges

Flange Depth:

0.423 inches all flanges and 0.453 inches all flanges

Flange Connecting Hole Diameter:

0.169 inches all flanges all connection facilities and 0.172 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.05

Insertion Loss In Decibels:

0.06

Waveguide Outside Width:

Between 1.246 inches and 1.254 inches

Waveguide Inside Width:

Between 1.118 inches and 1.126 inches

Waveguide Inside Height:

Between 0.493 inches and 0.501 inches

Waveguide Outside Height:

Between 0.621 inches and 0.629 inches

Waveguide Longer Offset Distance:

4.120 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Offset Distance:

1.600 inches

Flexibility:

Flexible single tubing segment

Material:

Rubber natural single tubing jacket

Precious Material And Location:

Internal surfaces silver

Precious Material:

Silver

Surface Treatment:

Silver single tubing segment outside surfaces

Style Designator:

Bend type

Fsc Application Data:

Antennas, waveguies, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0