

View Online at <https://aerobasegroup.com/nsn/5985-00-007-7210>

Application Design:

Audio

Schematic Diagram Designator:

"t"

Distance Between Mounting Facility Centers:

1.500 inches

Operating Temperature Range:

+0.0/+60.0 degrees celsius

Power Rating:

600.0 milliwatts average

Mounting Facility Screw Thread Series Designator:

Unc

Overall Attenuation Range In Decibels:

+0.0 to 80.0

Attenuation Variation Method:

Stepped

Step Position Quantity:

18

Attenuation Per Step In Decibels:

10.0

Mounting Facility Type And Quantity:

2 threaded hole

Overall Attenuation Accuracy In Decibels:

-0.50 to 0.50

Mounting Thread Quantity:

32 per inch

Adjustment Device Type And Quantity:

2 shaft

Mounting Facility Pattern:

Two position in-line

Shaft Type:

Round

Mounting Facility Screw Thread Diameter:

0.164 inches

Impedance Rating In Ohms:

1000.0 input-output

Test Data Document:

69526-82340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

Terminal Type And Quantity:

6 tab, solder lug

Fsc Application Data:

Antennas, waveguides, and related equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A223a0