

View Online at <https://aerobasegroup.com/nsn/5985-00-007-7210>

**Application Design:**

Audio

**Schematic Diagram Designator:**

"t"

**Distance Between Mounting Facility Centers:**

1.500 inches

**Operating Temperature Range:**

+0.0/+60.0 degrees celsius

**Power Rating:**

600.0 milliwatts average

**Mounting Facility Screw Thread Series Designator:**

Unc

**Overall Attenuation Range In Decibels:**

+0.0 to 80.0

**Attenuation Variation Method:**

Stepped

**Step Position Quantity:**

18

**Attenuation Per Step In Decibels:**

10.0

**Mounting Facility Type And Quantity:**

2 threaded hole

**Overall Attenuation Accuracy In Decibels:**

-0.50 to 0.50

**Mounting Thread Quantity:**

32 per inch

**Adjustment Device Type And Quantity:**

2 shaft

**Mounting Facility Pattern:**

Two position in-line

**Shaft Type:**

Round

**Mounting Facility Screw Thread Diameter:**

0.164 inches

**Impedance Rating In Ohms:**

1000.0 input-output

**Test Data Document:**

69526-82340 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing)

**Terminal Type And Quantity:**

6 tab, solder lug

**Fsc Application Data:**

Antennas, waveguides, and related equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A223a0