NSN 5985-00-008-2029

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-008-2029

Cross Sectional Shape:

Internal, rectangular external, rectangular

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

0.705 inches all flanges and 0.707 inches all flanges

Flange Inside Height:

0.394 inches all flanges and 0.396 inches all flanges

Flange Outside Width:

1.298 inches all flanges and 1.328 inches all flanges

Flange Outside Height:

1.298 inches all flanges and 1.328 inches all flanges

Flange Depth:

0.298 inches all flanges and 0.328 inches all flanges

Flange Connecting Hole Diameter:

0.144 inches all flanges all connection facilities and 0.147 inches all flanges all connection facilities

Voltage Standing Wave Ratio:

1.10

Insertion Loss In Decibels:

0.20

Waveguide Outside Width:

Between 0.699 inches and 0.705 inches

Waveguide Inside Width:

Between 0.6195 inches and 0.6245 inches

Waveguide Inside Height:

Between 0.3085 inches and 0.3135 inches

Waveguide Outside Height:

Between 0.388 inches and 0.394 inches

Flange Connecting Facility And Quantity:

4 unthreaded hole all flanges all connection facilities

Flange Style:

Cover type all flanges

Waveguide Leg Length:

Between 0.940 inches and 1.180 inches

Waveguide Longer Leg Length:

Between 1.912 feet and 1.922 feet

Waveguide Center To Center Distance:

Between 3.000 inches and 3.120 inches

Waveguide Height:

Between 1.928 feet and 1.938 feet

NSN 5985-00-008-2029 Waveguide Assembly - Page 2 of 2



Flexibility:
Rigid single tubing segment
Material:
Copper alloy all tubing segment and flange
Surface Treatment:
Any acceptable all tubing segment and flange all surfaces
Style Designator:
U-bend type
Fsc Application Data:
Antennas, waveguides, and related equipment
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
Yes - demil/mli

Fiig: A073a0