NSN 5985-00-008-2451

Waveguide Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-008-2451

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Corrugated single tubing segment

Flange Quantity:

2

Flange Inside Width:

3.002 inches second flange

Flange Inside Height:

1.502 inches second flange

Flange Outside Diameter:

5.313 inches second flange

Flange Depth:

1.250 inches second flange

Flange Connecting Hole Diameter:

0.256 inches second flange all connection facilities

Voltage Standing Wave Ratio:

1.20

Insertion Loss In Decibels:

0.10

Maximum Operating Pressure:

26.0 pounds per square inch gage

Waveguide Outside Width:

3.000 inches

Thread Size:

0.250 inches first flange all connection facilities

Waveguide Inside Width:

2.840 inches

Waveguide Inside Height:

1.340 inches

Waveguide Outside Height:

1.500 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Length:

2.666 feet

NSN 5985-00-008-2451 Waveguide Assembly - Page 2 of 2



| Flexibility: |
|---|
| Flexible single tubing segment |
| Material: |
| Plastic single tubing jacket |
| Surface Treatment: |
| Chromate all tubing segment and flange outside surfaces |
| Style Designator: |
| Straight type |
| Thread Series Designator: |
| Unc first flange all connection facilities |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |

A073a0