

View Online at <https://aerobasegroup.com/nsn/5985-00-008-8379>

Thread Class:

2b mounting facility hole

Body Style:

Rectangular

Overall Length:

1.066 inches

Overall Height:

0.562 inches

Overall Width:

0.480 inches

Frequency Rating:

24.0 megahertz and 38.3 megahertz single frequency voltage standing wave ratio

Switch Type:

Nontransfer

Longest Horizontal Distance Between Mounting Centers:

0.866 inches single mounting facility pattern

Longest Vertical Distance Between Mounting Centers:

0.362 inches single mounting facility pattern

Operating Temperature Range:

+0.0 to 75.0 degrees celsius

Voltage Standing Wave Ratio:

1.20 single

Insertion Loss In Decibels:

2.00 single

Rf Power Handling Capability:

1.0 watts peak single

Minimum Crosstalk Rating In Decibels:

30.0 single

Actuator Operating Method:

Relay

Actuator Current Type And Rating In Amps:

0.2 dc

Actuator Voltage In Volts:

28.0

Switch Operation Sequence:

Makes before breaks

Switching Time:

0.25 microseconds

Switch Return Mechanism Type:

Fail-safe

Pole Quantity:

1

Throw Quantity:

1

Coupling Position Quantity:

6

Mounting Facility Type And Quantity:

4 threaded hole

Thread Size:

0.112 inches mounting facility hole

Mounting Facility Pattern:

Four position rectangular single mounting facility pattern

Material:

Metal body

Thread Series Designator:

Unc mounting facility hole

Terminal Type And Quantity:

6 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A158a0