NSN 5985-00-009-6715

Fixed Attenuator - Page 1 of 2





Application Design: Transmission line **Body Material:** Brass **Body Style:** Round, terminal/terminals in opposite surface **Body Surface Treatment:** Silver plated, qq-s-365 **Overall Length:** 2.600 inches **Overall Diameter:** 0.562 inches **Operating Tempurature Range:** -55.0/+150.0 degrees celsius **Voltage Standing Wave Ratio:** 1.30 Input Impedance Rating In Ohms: 75.0 **Output Impedance Rating In Ohms:** 75.0 **Coaxial Connector Series Designation:** Bnc **Power Rating:** 2.0 watts average and 2.0 kilowatts peak **Rf Signal Attenuation In Decibels:** 3.0 Voltage Standing Wave Ratio Frequency Range: +0.0/+2.0 gigahertz **Attenuation Accuracy In Decibels:** -0.50/+0.50 **Mounting Method:** Connector **Terminal Type And Quantity:** 2 connector Frequency Range: Between 0.000 hertz and 2.000 gigahertz **Special Features:** P/n 612-3-2 supplied with female adaptor to accommodate the different connection type of the male/female input-output Shelf Life: N/a Unit Of Measure:

NSN 5985-00-009-6715

Fixed Attenuator - Page 2 of 2

Demilitarization:

No

Fiig:

A20000

