## NSN 5985-00-009-7639

Variable Attenuator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5985-00-009-7639

Application Design:
Waveguide
Body Style:
Waveguide type
Overall Length:
4.750 inches
Bolt Circle Diameter:
4.375 inches
Overall Height:
4.750 inches
Overall Width:
3.536 inches
Scale Linearity:
Linear
Scale Division Quantity:
43
Shaft Diameter:
Between 0.248 inches and 0.251 inches
Shaft Length:
0.820 inches
Unthreaded Mounting Hole Diameter:
0.209 inches
Operating Tempurature Range:
+0.0/+71.0 degrees celsius
Voltage Standing Wave Ratio:
1.15
Power Rating:
400.0 milliwatts average
Waveguide Flange Type:
Cover
Waveguide Flange Designation:
Ug-419/u
Insertion Loss At Minimum Attenuation In Maximum Decibels:
0.5
Overall Attenuation Range In Decibels:
+0.0 to 40.0
Attenuation Accuracy Reference Frequency:
13.38 gigahertz
Attenuation Variation Method:
Continuous
Mounting Facility Type And Quantity:

3 unthreaded hole

## **NSN 5985-00-009-7639** Variable Attenuator - Page 2 of 2



Frequency Range:
Between 13.270 gigahertz and 13.380 gigahertz
Overall Attenuation Accuracy In Decibels:
-0.50/+0.50
Adjustment Device Type And Quantity:
1 shaft
Mounting Facility Pattern:
Three position circular
Shaft Type:
Round
Terminal Type And Quantity:
2 flange
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No Fiig: A223a0