

View Online at <https://aerobasegroup.com/nsn/5985-00-014-2669>

Cross Sectional Shape:

Internal, rectangular external, rectangular

Thread Class:

2b first flange all connection facilities

Thread Direction:

Right-hand first flange all connection facilities

Tubing Wall Construction Style:

Seamless single tubing segment

Flange Quantity:

2

Flange Inside Width:

2.002 inches second flange and 2.005 inches second flange

Flange Inside Height:

1.002 inches second flange and 1.005 inches second flange

Flange Outside Diameter:

3.610 inches second flange and 3.640 inches second flange

Flange Depth:

0.922 inches first flange and 0.953 inches first flange

Flange Connecting Hole Diameter:

0.199 inches second flange all connection facilities and 0.203 inches second flange all connection facilities

Thready Qty Per Inch (tpi):

32 first flange all connection facilities

Maximum Operating Pressure:

40.0 pounds per square inch gage

Waveguide Outside Width:

Between 1.995 inches and 2.005 inches

Thread Size:

0.190 inches first flange all connection facilities

Waveguide Inside Width:

Between 1.867 inches and 1.877 inches

Waveguide Inside Height:

Between 0.867 inches and 0.877 inches

Waveguide Outside Height:

Between 0.995 inches and 1.005 inches

Flange Connecting Facility And Quantity:

8 unthreaded hole second flange all connection facilities

Flange Style:

Cover type second flange

Waveguide Center To Center Distance:

9.375 inches

Waveguide Height:

2.875 inches

Special Features:

Flange faces free of paint, 63.0 in. Microinch finish

Flexibility:

Rigid single tubing segment

Material:

Aluminum alloy single tubing segment and flange

Surface Treatment:

Oxide film all tubing segment and flange inside surfaces

Style Designator:

Double bend type

Thread Series Designator:

Unf first flange all connection facilities

Fsc Application Data:

Antennas, waveguides, and related equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A073a0